

CLEAR ACRYLIC SEALER

244 TUFSEAL

S U R F A C E P R O T E C T I O N

LANKO



CHARACTERISTICS

- Prevents migration of water stains, dirt, oil and grease.
- Non-yellowing when exposed to UV
- Excellent water repelling characteristic.
- Unaffected by most alkali, mild acid, oil, grease, detergent and some mild solvent.

COVERAGE

Coverage will depend on the texture and porosity of the surface. As a guide, one litre will cover approximately 10-15 m² on concrete surface

PACKAGING

- 1 litre container

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

244 TUFSEAL is a highly durable non-yellowing clear acrylic sealer and unaffected by most alkali, mild acid, oil, grease, detergent and some mild solvent.

244 TUFSEAL protects substrate against deterioration, weathering and carbonation.

USES

- As a protective sealer on unglazed quarry tiles, slates, pavers, roof tiles, marble, terrazo.
- As a dustproofer onto concrete, precast concrete, masonry.
- As a water repellent protection to brickwall and fairface brickwall.
- Seals porous surface to prevent fungus and algae growth.

WORK INSTRUCTIONS

Substrate preparation

- For new or old substrates, surfaces should be free from dirt, grease, fungus/algae and any loose matter. Surface should be dry and free from stains.
- New concrete surface should have a minimum of 7 days curing period before applying 244 TUFSEAL.

Product preparation

- No mixing is required, just stir the material before use to prevent settlement due to storage and transportation.
- Apply 244 TUFSEAL directly from the container.

Application

- Apply a minimum of 2 coats using brush, roller or spray.
- Ensure the surface is dry before applying 244 TUFSEAL.
- Allow the sealer to dry before trafficking.
 - Tack free-approx. 30 minutes.
 - Trafficable-approx. 2 hours. after the 2nd coats was applied

PRECAUTIONS

- Temperature range for use : 5°C - 35°C.
- Clean tools with turpentine before the product dries.
- Store in frost-free conditions.
- Avoid frost in the 24 hours following application.
- Do not work in direct sunlight or apply to a hot substrate.
- Do not apply during rainfall or apply to a damp or wet substrate.
- Gloves and eye protection should be worn by persons with sensitive skin.



www.parexgroup.co.th

"The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document."

ParexGroup Company Limited

183 Regent House Building, Rajdamri Road, Lumpini, Pathumwan, Bangkok 10330 Tel. 66 (0) 2651 9838 Fax. 66 (0) 2651 8003

PAREXGROUP
Building expertise, together