

## Wash Primer W

### One-component, water-based primer

---

#### Fields of application

**Wash Primer W** is a one-component, water-based primer, with very strong adhesion on glossy surfaces such as aluminum, galvanized substrates.

---

#### Properties

- It exhibits high adhesion strength
- It is environmentally friendly, user friendly and non-toxic

---

#### Technical characteristics

**Consumption** 95-115ml/m<sup>2</sup> (for one coat).

**Drying time** 1 h (+25°C)

**Dry to recoat** 24 h (+25°C)

**Temperature of application** >+10°C

Low temperatures and humidity prolong drying time.

---

#### Instructions for use

The surface should be dry, free from dust, dirt, greasy and oily substances. Therefore, it should be brushed, grinded and after that cleaned with solvent **Neotex<sup>®</sup> 1021**. Add water up to 15-20%. It can be applied by roller suitable for enamel paints.

---

#### Notes

- The material should not be applied under conditions of high humidity
- Surfaces must be completely dry (moisture content <4%) during the application and the relative ambient humidity less than 65%
- The material must be applied in a thin and single layer
- When intended to be covered with material containing solvent, recoating should take place 36 hours

---

#### Cleaning of tools

Use water immediately after application.

---

#### Packing

Tin cans 1 lit.

---

#### Storage stability

1 year in its unopened, original container in absolutely dry place protected from direct sunlight and low temperatures.

---