NEOTEX® S.A.
ESTABLISHED IN 1959
CONSTRUCTION CHEMICALS
www.neotex.gr • e-mail: neotex@neotex.gr
ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.:+30 210 5557579, FAX: +30 210 5558482
THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.:+30 2310 467275, FAX: 2310 463442

Neotex® 1021

Thinner for epoxy & PU paints

Fields of Application	Thinner suitable for epoxy systems **Neopox® Special, Neopox® Pool, Neopox® Pro, Neopox® Satine, Neopox® Deco, Epoxol® Primer** and polyurethane systems **Neodur®, Neodur® Varnish** and **Neodur® Varnish Mat.** Also suitable for the cleaning of the surfaces or tools, after the application of the above products.

Technical Characteristics

Appearance	Transparent liquid
Density	0,87 kg/l

Packing	Cans of 1L, 5L and 20L
Storage Stability	2 years in sealed tin cans kept in shade and away from combustive sources.
Safety Precautions	See Safety Data Sheets.

The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX® SA .It is offered as a service to designers and contractors in order to help them find potential solutions. However, as a supplier, NEOTEX® SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition.